



Mieux Electronic Ultra Podium

Our Mieux Electronic Podium is an integrated system of audio-visual equipment that facilitates the delivery of smart lectures and presentations. It is also possible to integrate a document camera with Mieux Podium to visualize and record activities in the classroom or conference room. For interactive lectures or presentations, our podium is an essential component of any smart classroom or conference room. This system provides multimedia presentations and lectures, enhances two-way interaction between presenter and audience, provides a truly remarkable learning experience, integrates all equipment, has a robust and sophisticated design etc.

Area Of Applications

Training room



Classroom



Auditorium



Mieux Electronic Podium

Product Specifications	
Body Material	
Body	: Metallic
Top	: Metallic
Top Sliding Mechanism	: Yes
Provision for Monitor	: Yes (upto 22 inches)
Document Camera Tray	: Yes (Sliding Type)
Electronic Monitor Lift	: Yes
Monitor Features	
Screen Size	: 21.5" LED
Resolution	: 1920 x 1080
PC Connection	: USB Port
Luminosity	: 250 cd/m2
Input	: HDMI
Number of Colours	: 16.7M
Response time	: 5ms
Contraste ratio	: 1000:1
Operating System	: Windows, Linux, Mac.
Electrical	
Input Voltage	: DC 12V
Power	: 100 – 250V AC.
Digital Signal Processor (Optional)	
Frequency Range	: 30Hz -15000 Hz
Automatic Echo Cancellation	: Yes
Automatic Gain Control	: Yes
Dynamic Noise Reduction	: Yes
Full Duplex	: Yes
Line Input	: 1x Line Input
Line Output	: 1 x Line Output
USB Audio Port	: 1 x USB Port
Package Includes	
Microphone Options	: 1 lapel + 1 Handheld
Frequencies Response	: 50 Hz-18000 Hz
Antennas	: 2 x 3dBi
Output	: Balanced Out x2, Mixed Out x 1
Volume Control	: Yes
Amplifier	: Yes
Line Input	: 1x Balanced, 2 x Unbalanced.
Phantom	: Yes (15 V for Balanced Input)
Power output @8 ohms	: 50 Watts x 2
Minimum impedance	: 8 Ohm
Frequency response	: 20Hz-20000Hz
Speakers (1Pair)	: 50 Watts Speaker (1" Titanium Dome Tweeter, 5.25" Polypropylene Woofer, 90-20KHz Frequency response)
Central Controller	
Ethernet	: 1x RJ-45
RS-232 Port	: Total 1 dedicated RS-232 Port
Relay Switch Port	: Screen Up/Screen Down (2 Nos)
Gooseneck Microphone Features: (Optional)	
Cartridge	: 20mm Condenser
Frequency Response	: 40–20000 Hz.
Polar Pattern	: Cardioids
Connectors	: 3-Pin XLR
Control Pad	
Type	: Buttonpad
Interface :	: RS-232
Power	: 12V
Size	: N/A
Type	: Buttonpad with Buttons: VGA, HDMI, PC, Screen up/ Screen Down, Projector Lift up, Projector Lift Down, Mic Mute/ Unmute, Volume Mute/Unmute, Volume Up/Down.
Laptop Interface	
Laptop Interface	: Inbuilt
Video Port For laptop	: 1 x VGA, 2 x HDMI
Audio Port For Laptop	: 1 x 3.5mm Stereo Female Port
LAN Port	: 1 x RJ-45
USB Ports	: 4 x USB 2.0 Ports, 1 x USB 3.0 Ports, 1 x USB (Laptop Touch & DSP), 1 x USB (CPU Touch & DSP)
Power Socket	: 3 Pin AC 220 Power Socket
RS-232 Port	: 1 x 3 Pin RS-232 Ports, 1 x 9 Pin RS-232 Port.
Video Input Ports	: 2 HDMI x Laptop, 1 HDMI x PC, 1 HDMI x Visualiser
Switcher	: Inbuilt 4 HDMI Input, 2 HDMI Output, 1 VGA Output
CPU (Optional)	
Processor	: Intel i3 / i5
RAM	: 4 GB
HDD	: 1000 GB
Operating System	: Windows 10
Keyboard/Mouse	: Yes
CONTENTS	
Accessories	: 1.5 Mtrs HDMI Cable x 2, 3.5 mm Male to Male x 1, 1.5 mtrs USB 2.0 M to M x 4.

*Due to continuous product development, the specifications/colour may change without prior intimation.



Distributed And Marketed By

Mieux Display Private Limited

207, 2nd Floor, Red Rose Building, 49-50, Nehru Place, 110019, New Delhi