




Mieux PTZ (Pan-tilt-zoom) Camera

Features



» **2.07M Pixel**



» **12x Optical Zoom**



» **Tilt $\pm 30^\circ$, Pan $\pm 170^\circ$**



» **255 Presets**



» **16x Digital Zoom**



» **Plug and Play**

Tilt $\pm 30^\circ$ Pan $\pm 170^\circ$

HFoV 72.5°

Up to 255 presets



Tilt $\pm 30^\circ$



HFoV 72.5°



Pan $\pm 170^\circ$



Mieux PTZ (Pan-tilt-zoom) Camera

Product Specifications	
Camera Parameters	
Pixel	2.07 M
Video System	1080P, 720P, 540P, 480P, 360P, 240P etc.
Sensor	1/2.7inch, CMOS
Scanning Mode	Progressive
Lens	12x, f3.5mm~42.3mm, F1.8 ~ F2.8.
Digital Zoom	16x
Minimal Illumination	0.5 Lux @ (F1.8, AGC ON)
Shutter	1/30s~1/10000s
White Balance	Auto, Indoor, Outdoor, One Push, Manual, VAR(2500K~8000K).
Backlight Compensation	Support
Digital Noise Reduction	2D & 3D Digital Noise Reduction.
Video S/N	≥55dB
Horizontal Angle of View	72.5°~ 6.9°
Vertical Angle of View	44.8°~ 3.9°
Horizontal Rotation Range	±170°
Vertical Rotation Range	-30°~ +30°
Pan Speed Range	1.7°~ 100°/s
Tilt Speed Range	0.7°~ 28°/s
H & V Flip	Support
Image Freeze	Support
Number of Preset	255
Video Format	YUY2 (BULK): max to 1080P@30fps YUY2 (ISOC): max to 1080P@30fps H.264 AVC: max to 1080P@30fps H.264 SVC: max to 1080P@15fps MJPEG: max to 1080P@28fps
Preset Accuracy	0.1°
I/O Ports	
USB 3.0	1
RS232 IN	1
RS232 OUT	1
DC IN	1
USB Featured	
Operating Systems	Windows 7, Windows 8, Windows 10, Mac OS X, Linux, Android
Color System / Compression	YUV 4:2:2 / H.264 / MJPEG
Physical Specifications	
Dimension L×H×D	128.5×118×156.2mm
Net Weight	0.91Kg
Power	
Input Voltage	DC 12V
Current Consumption	1.0A (Max)
Power Consumption	12W (Max)
Environmental Conditions	
Operation Temperature	-10°C ~ 40°C
Storage Temperature	-40°C ~ 60°C

*Remark: Due to continuous product development, the specifications may change without prior intimation.

Distributed And Marketed By

Mieux Display Private Limited

207, 2nd Floor, Red Rose Building, 49-50, Nehru Place, 110019, New Delhi

