



Mieux Outdoor LED Video Wall



» **Fast & Easy Maintenance**



» **Thin & Lightweight**



» **Easy Endurance Of External Weather**



» **Dynamic Visual Experience**



» **High Brightness**



» **Automatic Alignment Mechanism**

PRODUCT IMAGES



Mieux Outdoor LED Video Wall

Product Specifications				
Item	MX4p	MX6p	MX8p	MX10p
Pixel Configuration	SMD	SMD	SMD	SMD
Pitch(mm)	4	6	8	10
Module Weight(Kg)	0.46	0.47	0.46	0.49
Module Composition(W*H)	3x6	3x6	3x6	3x6
Unit Area(m ²)	0.9216	0.9216	0.9216	0.9216
Cabinet Weight(kg)/m ²	40	40	40	40
Pixel Density(Pixel/ m ²)	62500	27778	15625	10000
Surface Flatness(mm)	≤0.6	≤0.6	≤0.6	≤0.6
Brightness(Nits) (After Calibration)	5000-6500	5000-6500	5000-6500	5000-6500
IP Grade(Front/Rear)	IP65/IP54	IP65/IP54	IP65/IP54	IP65/IP54
Color Temperature(K)	3000-10000 Adjustable			
Horizontal Viewing Angle(°)	160	160	160	160
Vertical Viewing Angle(°)	140	140	140	140
Deviation of LED Luminance Center (After Calibration)	≤3%	≤3%	≤3%	≤3%
Brightness Uniformity	≥97%	≥97%	≥97%	≥97%
Chromaticity Uniformity (After Calibration)	±0.003Cx,Cy Within			
Contrast Ratio	5000:1	5000:1	5000:1	5000:1
Average Power Consumption (W/m ²)	283	267	300	265
Max Power Consumption (W/m ²)	850	800	900	800
Power Supply	AC100~240V (50/60Hz)			
Drive Mode	Constant Current Drive			
Refresh Rate(Hz)	≥3840/≥1920	≥3840/≥1920	≥3840/≥1920	≥3840/≥1920
Frame Rate(Hz)	50&60	50&60	50&60	50&60
Lifetime(hrs)	100,000	100,000	100,000	100,000
Operation Temperature(°c)	-20~40	-20~40	-20~40	-20~40
Storage Temperature (°c)	-30~60	-30~60	-30~60	-30~60
Storage Humidity(RH)	10~85% No Condensation			
Operation Humidity(RH)	10~80% No Condensation			

Remark: Due to continuous product development, the specifications may change without prior intimation.

Distributed And Marketed By

Mieux Display Private Limited

207, 2nd Floor, Red Rose Building, 49-50, Nehru Place, 110019, New Delhi