



Mieux Interactive Flat Panel



» **Android 11 System**
4GB RAM + 32GB ROM



» **Zero Air Gap Bonding Technology**
Eliminate the viewing angle deviation caused by light refraction.



» **Screen Share**
Support wireless screen mirroring by PC, laptop, tablet, smart phone.



» **Eco & Eye Protection**



» **4K point-to-point display**
Fluent and UHD transmission, more delicate image and handwriting display.



» **Palm Erase**
Writers can easily erase the content with their palm.



» **Optional OPS**
i5, 10th Gen or higher, 8 GB, 128/256 GB SSD, Windows 10 pro (Optional)



» **Smart writing with dual Operating System**



Mieux Interactive Flat Panel

Specification	Type	Parameter		
Panel	Display Size	65"	75"	86"
	Panel Standard	A Grade		
	Light Source	LED		
	Resolution	3840 * 2160 Pixels		
	Brightness	400		
	Contrast Ratio	1200:1		
	Contrast Ratio (typ.)	5000:1		
	Frequency	60 Hz		
	Viewing Angle	178°(H)/ 178° (V)		
	Life Span	50,000 Hrs (min.)		
	Response Time	6 ms		
	Color Saturability	70%		
	Display Colors	1.07B (10 bit)		
Android System	Processor	CPU	A55*4	
		GPU	Mali G52MP2	
	Memory	DDR4: 4GB eMMC: 32GB		
	System Version	Android 11.0		
	Wi-Fi	2.4G/5G		
	Bluetooth	5.0		
Power Environment	Voltage	AC100-240 V~, 90-264 V~50/60 Hz		
	Speaker	15W*2		
	Power Supply (AC) Input	100-240V		
	Working Temperature	0°C~40°C		
	Storage Temperature	-20°C~60°C		
Working Humidity	10%~90% No Condensation			
Input & Output Ports	RS-232	1		
	VGA In	1		
	RJ45	2		
	Audio In	1		
	Audio Out	1		
	HDMI In	2		
	HDMI Out	1		
	USB 2.0	2		
	USB 3.0	2		
SPDIF	1			
Front Port Interface	Power Button	1		
	USB 3.0	2		
	HDMI In	1		
	Touch USB	1		
OPS (Optional)	USB	USB 2.0*2; USB 3.0*2		
	RJ45	1		
	HDMI Out	1		
	Audio In	1		
	Audio Out	1		
	DP Out	1		
Structure	Shell Material	Aluminum Alloy Frame, Sheet Metal Back Cover		
Touch	Touch Specifications	Infrared Sensing Technology, Support 20 Touch & 10 Writing Points.		
	Glass	4mm Anti-Glare, Physical Tempered Mohs level 7 Explosion-Proof		
	Glass Transmittance	>92 %		
	Frame Material	Aluminum Alloy Frame, PCBA		
	Touch Accuracy	≤ 1mm		
	Touch Depth	3 ± 0.5 mm		
	Input Mode	Opaque Object (Finger, Pen, etc.)		
	Power Supply	USB		
	Supply Voltage	DC 5.0 ± 5%		
Accessory	Remote	1		
	Power Cord	1		
	Touch Pen (Double Pen Tip)	2		

*Remark: Due to continuous product development, the specifications may change without prior intimation.

Distributed And Marketed By

Mieux Display Private Limited

207, 2nd Floor, Red Rose Building, 49-50, Nehru Place, 110019, New Delhi.

