



Mieux Indoor LED Video Wall



» **Fast And Easy Maintenance**



» **Automatic Alignment Mechanism**



» **Flexible Installation**



» **Thin And Lightweight**

PRODUCT IMAGES



Mieux Indoor LED Video Wall

Product Specifications				
Item	MX015p	MX025p	MX03p	MX04p
Pixel Configuration	SMD	SMD	SMD	SMD
Pitch (mm)	1.538	2.5	3	4
Module Resolution (WxH)	208*104	128x64	64x64	80x40
Module Size (mm) (WxHxD)	As Per The OEM			
Module Weight (Kg)	0.30	0.30	0.24	0.30
Module Composition (WxH)	2*3	2*4	3*3	2*4
Cabinet Resolution (WxH)	416*312	256*256	192*192	160*160
Cabinet Size (mm) (WxHxD)	As Per The OEM			
Unit Area m ²	0.30	0.41	0.33	0.41
Cabinet Weight (kg/m ²)	24	32	32	32
Pixel Density (pixel/m ²)	422500	160000	111111	62500
Surface Flatness (mm)	≤0.3	≤0.3	≤0.3	≤0.3
Brightness(nits) (after calibration)	600-800			
Color Temperature (K)	3000-10000 Adjustable			
Horizontal Viewing Angle (°)	160	160	160	160
Vertical Viewing Angle (°)	140	140	140	140
Deviation of LED Luminance Center (After Calibration)	≤3%	≤3%	≤3%	≤3%
Brightness Uniformity	≥97%	≥97%	≥97%	≥97%
Chromaticity Uniformity (After Calibration)	±0.003Cx, Cy within			
Contrast Ratio	5000:1	5000:1	5000:1	5000:1
Max Power Consumption (W/m ²)	450	480	480	480
Average Power Consumption (W/m ²)	150	160	160	160
Power Supply	AC100~240V (50/60Hz) Dual Power supply (Optional)			
Frame Rate (Hz)	50&60	50&60	50&60	50&60
Refresh Rate (Hz)	≥3840	≥3840	≥3840	≥3840
Lifetime (hrs)	100,000	100,000	100,000	100,000
Operation Temperature (°C)	-20~40	-20~40	-20~40	-20~40
Storage Temperature (°C)	-30~60	-30~60	-30~60	-30~60
Operation Humidity (RH)	10~80%	10~80%	10~80%	10~80%
Storage Humidity (RH)	10~90%	10~90%	10~90%	10~90%

Remark: Due to continuous product development, the specifications may change without prior intimation.

Distributed And Marketed By



Mieux Display Private Limited

207, 2nd Floor, Red Rose Building, 49-50, Nehru Place, 110019, New Delhi